

Data Cabling Specifications – Enhanced Category 5 UTP Cable

- 24 AWG, solid conductors
- 4-Pair cable:
- Meets or exceeds TIA/EIA-568-B Enhanced Category 5 ISO 11801:2002 class D specifications
- Independently verified by Intertek ETL SEMKO testing services
- Performance characterized to 200 MHz (minimum)
- 2dB NEXT performance above Category 5e
- UL & cUL Listed (CMR/CMP)
- Meets or exceeds all requirements for Gigabit Ethernet
- Lead-free jacketing

Data Cabling Specifications – Enhanced Category 5 UTP Jack With Face Plates and Mounting Box

- Thin profile improves outlet density
- Modular jacks available with integral dust covers
- 180° or 90° cable dress for easy termination
- Universal wiring label permits wiring to T568A or T568B
- Meet or exceed all TIA and ISO component performance requirements
- Bend-limiting strain relief included with unshielded jacks
- UL Listed: E81956
- 8-Position RJ45 modular jacks for 1-, 2-, 3- and 4-pair applications

Data Cabling Specifications – Enhanced Category 5 Patch Leads

- Meet or exceed Category 5e Performance Standards
- 4-Pair stranded unshielded, 24 AWG conductors
- Booted cable assemblies include color-matched snagless boots
- Universal wiring (works with both T568A and T568B)
- Minimum length should be 3m