

Specifications for Dot Matrix Printers (Narrow)

		Bidders Response	
Printing Method	24 Pin Impact Dot Matrix.		
Speed	Not less than 300 CPS at 10 CPI in draft quality not less than 200 CPS at 10 CPI in letter quality Bi-directional printing.		
Paper Width	Up to 10.1 inches		
Printing Width	80 characters in 10 CPI pitch.		
Paper Feed	Must be switch able between tractor feed and friction feed for continuous forms and for cut sheets.		
Character Set	96 standard ASCII and graphic characters.		
Quality	Draft and letter quality.		
Build in Fonts	In letter quality, Roman, Sans Serif, Courier and Prestige.		
Font Variation	Pitch 10, 12, 15, 20 CPI Line spacing variable form 1/6 inch. Normal, Emphasized, Bold, Italics, Upright Normal, Underlined, superscript subscript.		
Control Panel	Power on. On line, Font selection, Line Feed, Form feed, Load / Eject buttons, LCD display and LED indicators for power, line on and paper out.		
Buffer	64 KB or higher		
Ribbon Life	2 million characters for black ribbon		
Cables	The parallel printer connector and USB cable. Power cord for plugging into a standard 230V / 50 Hz A.C. Power Supply: 230V / 50 Hz. A.C.		
Interface	Parallel, USB		
Warranty Maintenance	Warranty shall cover the whole system for 1 year including printer head. Maintenance charges offered after the warranty period should be specified by the vendor.		