Load Balancing (Normal) Router - Specifications	
Brand	(Specify)
Model	(Specify)
Country of Origin	(Specify)
Country of Manufacture	(Specify)
WAN	2-port 10/100Mbps RJ-45 Auto Negotiation (802.3u)
LAN	4-port 10/100Mbps RJ-45 Auto-MDI/MDIX; 802.3/802.3u
Outbound Load Balance & Backup	Outbound load balance by bytes, packet, & session Auto backup connection
Protocols	Security: NAT, CHAP Network: TCP/IP, HTTP, DHCP, PPP, UPAP, PPPoE Multi-session PPPoE, ICMP, ARP proxy Connection: Static IP, Dynamic IP, PPoE, PPTP
VPN	PPTP & IPSec pass through
Firewall	NAT (Network Address Translation) NAPT (Network Address Port Translation) DoS (Denial of Service) Access control by group ICMP filter for WAN Ping to Death Port Scan Packet filter URL block
Security	Admin passwords Authentication with UPAP and CHAP for PPPoE
Management	Management through WAN & LAN port HTTP web based management Syslog Support with H.323 VoIP products Multi-session PPPoE SMTP bind SNMP UPnP NAT status & connection list Virtual server Multi-DMZ MTU changeable for WAN Dial-on-demand & Auto-disconnect Dynamic DNS MAC address clone QoS
Firmware upgrade	HTTP web based download TFTP download
Warranty	Comprehensive warranty shall cover the item for 1 year (All charges, material, labor and other incidentals have to be borne by the supplier during the warranty)